

SAINS GAS BUTANE GAS CARTRIDGE (CE Approved)



BUTANE GAS CARTRIDGE

Gas purity: $\geq 95\%$
Can size: 65mm*185 \pm 0.2ml
Can net weight: 95g \pm 5g
Wall thickness: Body: 0.20mm
Top cover: 0.33mm
Bottom Cover: 0.35mm
Gas net weight: 220g, 227g, 230g and 250g.
Working pressure: 0.2Mpa-0.3Mpa
Deformation pressure: 1.4Mpa-1.5Mpa
Burst pressure: 1.7Mpa
Manufacturing Standards: EN417-2012

- High purity butane gas
- Burns without impurities
- Easy to carry
- Blue flame
- Long burning time
- Comply with European standards

Application:

Use as portable stove fuel and torch fuel
Suitable for indoor and outdoor use
For cooking, grilling, or welding metal

Instructions for use:

Align the notch on the gas cylinder valve with the bayonet of the portable stove or torch valve. Once the connection is tight, it can be used for ignition.

Precautions:

The gas cylinder is a disposable product, please throw it away after use and cannot be refilled. It is prohibited to puncture or hammer the gas tank. If the gas tank leaks, stop using it immediately.

Store gas bottles in a cool and safe place below 50 degrees Celsius. Do not place gas bottles on induction cookers or in places where children can easily access them.

Packing:

4 PCS/Plastic wrap shrink packing
28pcs/Carton

20FT Container: 1030 cartons, 28840pcs
40HQ Container: 2400 cartons, 67200pcs

Can body pattern and carton pattern can be customized

www.sainsgas.com

Tel: +86 180 5323 6145

Qingdao Sains Gas Technology Co., Ltd